

RS PLUS-E tower





DSP-CONTROLLED ON-LINE UPS

1000VA ~ 3000VA



The RS PLUS-E tower is a sleek double conversion online UPS with premium features including a wide input voltage window and extended runtime capability for critical applications for IT equipment, routers, point of sales and servers.

PERFECT FOR:

- 
Routers
- 
PC & Networks
- 
Switches
- 
IT loads & servers

FEATURES

- Online double conversion VFI protection from 1000VA to 3000VA
- Extreme battery lifetime thanks to:
 - Wide input voltage tolerance (110-300V)
 - Wide input frequency (44-66Hz)
 - Intelligent battery management
- Optimized Output Power Factor 0.9
- Cold start to activate loads without mains
- Strong overload capability to improve Circuit Breaker's selectivity
- Intuitive LCD interface provides clear information with easy to use navigation keys
- UPS management via RS232 port or USB port
- Multiple outlets types: IEC, Schuko, Universal for various output connection
- Firmware upgradeable for updates and customization

OPTIONS


- External Battery Connector for extended runtime capability
- External matching battery cabinet
- Mini SNMP card to support real-time and web monitoring via TCP/IP

WHAT'S IN THE BOX


- Input power cable
- Output power cable (IEC C13 to IEC C14)
- Other Cables and Accessories are sold separately

BACK PANEL


RS Plus 1000E



RS Plus 2000E



RS Plus 3000E



SPECIFICATIONS

MODEL		RS PLUS 1000E		RS PLUS 2000E		RS PLUS 3000E	
INPUT	Input Voltage	220/230/240Vac					
	Voltage Range*1	110~300Vac					
	Phase	Single Phase with Ground					
	Frequency Range	44~66Hz (Auto sensing)					
	Input Power Factor	>0.98 @ 100% linear load					
OUTPUT	Capacity	1000VA/900W		2000VA/1800W		3000VA/2700W	
	Output Voltage	220/230/240 Vac (Settable)					
	Output Power Factor	0.9					
	Output Voltage Distortion	<4% @ 100% Linear load <7% @ 100% non-linear load					
	Output Voltage Regulation	±1%					
	Frequency Range	50Hz ±1Hz or ±3Hz (selectable)					
	Crest Factor	3:1					
	Transfer Time (AC to DC)	0ms					
	Output Waveform	Pure SineWave					
EFFICIENCY	Line Mode	>89%		>90%		>91%	
	Eco Mode	>96%		>96%		>96%	
BATTERY*4	Type	12V VRLA (Maintenance-free lead)					
	Number of Battery	2	3	4	6	6	
	Rated Battery Voltage	24Vdc	36Vdc	48Vdc	72Vdc	72Vdc	
	Uptime with internal battery at 100% load *3	≥ 5min					
	Recharge Time (to 90%)	4~6 hours					
	External Battery Connection	Option					
FRONT PANEL	LCD	Normal, Battery, Bypass, Self-Test, Battery Weak, Site Wiring Fault, Overload, Load/Battery Level					
	BUTTON (3 KEY)	ON/OFF / Enter / Function / Up / Down					
ALARM	Audible or Visual	Line failure/Battery low/Transfer to bypass/System fault					
PROTECTION	Full protection	Overload, Over Temperature, Short circuit, Deep discharge, Overcharge, Surge Protection					
FUNCTION	Multi-Mode	Normal/ECO					
	DC Start	Yes					
PHYSICAL	Dimension (WxHxD, mm)	147 x 224 x 308	147 x 224 x 388	192 x 250 x 386			
	Net Weight (kg)	8.3	10.8	16.0	20.2	20.5	
	Output Connections*2	3x IEC320-C13 + 1x Universal				3x IEC320-C13 + 2x Universal	
ENVIRONMENT	Operation Temperature	0~40°C					
	Operation Humidity	0%~90% (without condensing)					
	Altitude	1000m without derating					
	Noise Level	≤ 50dBA @ 1 meter front					
INTERFACE	Standard	RS-232, USB and EPO					
	Option	Mini SNMP/Web card					
	Compatible platforms	Microsoft Windows, Linux, Mac					
STANDARDS & CERTIFICATIONS	Safety & EMC	IEC EN 62040-1, IEC EN 62040-2					
	Marks	CE, FCC					

*Specifications subject to change without notice

*1) Based on load percentage

*2) Other outlet types are available upon request

*3) Battery capacity and configuration depends on the required uptime and load type.

*4) Ambient temperature for battery ≤ 25°C

Designed &
Engineered by:

